



VALENCIA DECO

STONE PRODUCTS
UNLIMITED, INC

Montauk, 6" x 6", Square Field Tile, POR-VALMON-66-M

VALENCIA DECO SQUARE

VALENCIA DECO 6" X 6"
SQUARE TILE IN PORCELAIN

STONE PRODUCTS
UNLIMITED, INC



Bridgeham

POR-VALBRI-66-M

Matte



Montauk

POR-VALMON-66-M

Matte



Noyack

POR-VALNOY-66-M

Matte



Clover B&W

POR-VALCLO-66-M

Matte



Kali Chic

POR-VALKAL-66-M


Matte



Providence

POR-VALPRO-66-M

Matte



Perla Chic

POR-VALPER-66-M

Matte

VALENCIA DECO 6" X 6" SQUARE TILE IN PORCELAIN

STONE PRODUCTS
UNLIMITED, INC

COLOR	SKU	TYPE	THICKNESS	PCS PER BOX	SQFT PER BOX	LBS PER BOX	EDGE	FINISH
Bridgeham	POR-VALBRI-66-M	Field Tile	9mm	44	10.23	37.25	Pressed	Matte
Montauk	POR-VALMON-66-M	Field Tile	9mm	44	10.23	37.25	Pressed	Matte
Noyack	POR-VALNOY-66-M	Field Tile	9mm	44	10.23	37.25	Pressed	Matte
Clover B&W	POR-VALCLO-66-M	Field Tile	9mm	44	10.23	37.25	Pressed	Matte
Kali Chic	POR-VALKAL-66-M	Field Tile	9mm	44	10.23	37.25	Pressed	Matte
Providence	POR-VALPRO-66-M	Field Tile	9mm	44	10.23	37.25	Pressed	Matte
Perla Chic	POR-VALPER-66-M	Field Tile	9mm	44	10.23	37.25	Pressed	Matte







Noyack, 6" x 6", Square Field Tile, POR-VALNOY-66-M



TECHNICAL INFORMATION

Tile collection performance based on industry standards.

PERFORMANCE CHARACTERISTICS

	Water Absorption	ASTM# RESULT	C648 < 0.5%
	Scratch Hardness	ASTM# RESULT	C373 7
	Breaking Strength	ASTM# RESULT	C373 > 275 lbs
	Shade Variation	Low (V2)	
	DCOF	ASTM# RESULT	- ≥ 0.42
	Chemical Resistance	ASTM# RESULT	C650 Resistant

APPLICATION

APPLICATION	DRY & LEVEL INTERIOR FLOOR	EXTERIOR FLOOR	EXTERIOR WALL	INTERIOR WALL	POOL LINING	COUNTERTOPS	SHOWER FLOOR	SHOWER WALL
RESIDENTIAL	X		X	X	X	X	X	X
COMMERCIAL	X		X	X	X	X	X	X

DISCOVER MORE AT:

WWW.SPUI.NET

Bridgeham, 6" x 6",
Square Field Tile, POR-VALBRI-66-M

Valencia Deco, Ver.23.12, Stone Products Unlimited | 5

**CHECK OUT
OUR PK ON
THIS COLLECTION**



WATCH HERE

